

Ultra-HD Wired Day/Night Outdoor Bullet IP Camera with Power over Ethernet (POE)

ENVIROMUX®

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
- Compatible with the E-2D/5D/16D, E-1W, E-MICRO-TRH(P), and E-MINI-LXO Environment Monitoring Systems.
 - With the E-2D/5D/16D, a triggered snapshot can be forwarded in alert emails or stored locally on a connected flash drive.
 - ◆ A snapshot can be triggered by any programmed event (motion detection, door open/close, glass break, smoke, liquid detection, etc.)
 - ONVIF authentication must be disabled on the camera.
- IR night vision supported up to 98.4 feet (30 m).
- 1/2.7" 5-Megapixel Progressive Scan CMOS sensor.
- Video Compression: H.265, H.264
- Max resolution and frame rate:
 - Main stream: 2592x1944 up to 20 fps, 2688x1520 up to 30 fps
 - Sub stream: 704x576 up to 25 fps, 704x480 up to 30 fps
- Lens: 2.8 mm (0.11 in).
- Viewing Angle: 103°
- System compatibility: ONVIF
- Built-in motion detection.
 - Auto-patrol preset positions: 4.
 - Camera sends snapshots via email when motion is detected.
- 10/100 Mbps Ethernet port for wired connections.
- Power:
 - Input: 100 to 240 VAC at 50 or 60 Hz
 - Output: 12 VDC, 1A external power adapter (included)
 - Max consumption: 5.6 W
 - Power over Ethernet standards supported: IEEE 802.3af
- Operating and storage temperature: -40 to 140°F (-40 to 60°C).
- Dimensions WxDxH: 2.76x6.54x2.76 in (70x166x70 mm).
- Waterproof rating: IP67
- Mounting hardware included.
- Regulatory approvals: CE, FCC, RoHS.



E-IPCAM-HNPO-P