

Low-Cost 2-Port Remote Power Reboot Switch with NEMA 5-15R Outlets

ENVIROMUX®

Remotely control power on/off/reboot to up to two servers, routers, web cams, firewalls, or other remote devices over IP.

- Auto-scheduler allows for scheduling power on/off/reboot events.
 - A delay can be set between the reboot of both outlets.
 - Up to 20 schedules can be set to power on or off specific ports at certain times.
- Multiple control options: Web interface, Google Hangouts, and command line interface using HTTP protocol.
- Control an unlimited number of Remote Power Reboot Switches from one Google Hangouts account.
 - Up to eight Google Hangouts users can control one Remote Power Reboot Switch.
 - Each Remote Power Reboot Switch must have its own Google Hangouts account.
 - Issue identical commands to multiple Remote Power Reboot Switches by creating Group Hangouts.
- Checks network connection and can automatically reboot device if there is no response.
- Auto-ping up to 5 IP addresses:
 - Automatically reboots selected port if there is no response.
- Send email alert notifications to any number of addresses.
 - User-specific alert notifications can be configured.
- Reset button for resetting the unit without unplugging the power.
 - The Remote Reboot Switch is the ideal solution for many applications, such as:
 - Remote reboot of any device, router, server, kiosk, etc. The device need not be network attached.
 - Secure sensitive devices by keeping them powered off when not in use. This prevents hackers from detecting them at all times.
 - Power down equipment when not needed for power savings and to save on wear and tear.
 - Power up alert devices like sirens, lamps, and messages, or environmental system like heaters, coolers, pumps, etc.



PWR-RMT-RBT2-515R-LC

- Remotely control power on/off/reboot two remote devices over IP
- Control via web interface, Google Hangouts, or command line interface
- Sends email alert notifications

The ENVIROMUX® 2-Port Remote Power Reboot Switch allows you to remotely reboot and control power (on/off) to up to two servers or other powered devices over IP.

Specifications

Power

- 100 to 250 VAC at 50 or 60 Hz.
 - 10A fuse.
- One USB Type A female port for optional USB power.
- Input connector: one IEC 320 C14 plug.
- Output connectors: two NEMA 5-15R receptacles.
- Includes 10A US line cord.

Network Interface

- One 10/100 Base-T Ethernet port with RJ45 Ethernet connector.
- 3 ft (1 m) CAT6 cable included.

Protocols

- HTTP, TCP/IP, DHCP, UDP, Dynamic DNS, SNTP.

Environmental

- Operating temperature: 32 to 140°F (0 to 60°C).
- Operating and storage relative humidity: 10 to 90% non-condensing RH.

Dimensions

- WxDxH: 5.1x5.1x1.75 in (130x130x44 mm)

Warranty

- Two years

Package Includes

- Remote Power Reboot Switch
- One power cord
- One 3-ft CAT6 cable
- Software & manual CD
- Quick installation guide

